



COMPONENT	MATERIAL & FINISH
MMSP BODY, CONTACTS, EMI & ANTI ROCK RINGS	BeCu, ASTM B196, UNS C17300 GOLD PLATE, MIL-G-45204, TYPE 1, GRADE C, CLASS 1
INSULATORS	PTFE, ASTM D1710, TYPE I, GRADE 1, CL A
SMA BODY	303 CRES, ASTM A582 GOLD PLATE, MIL-G-45204, TYPE 1, GRADE C, CLASS 1
SMA COUPLING NUT	303 CRES, ASTM A582 PASSIVATE, AMS-QQ-P-35
HEAT SHRINK TUBING	POLYOLEFIN AMS-DTL-23053/5 CL 1, BLK OR WH
LOCKRING	BeCu, ASTM B196, UNS C17300
GASKET	SILICONE RUBBER, ZZ-R-765C



MICRO-MODE PRODUCTS, INC.
The Reliable Connection to the Future

El Cajon, CA 92020
ph 619.449.3844
www.micromode.com

CAGE CODE
15907

ASSY PROCEDURES: N/A

INSERTION/EXTRACTION TOOL: N/A

SMP FEMALE TO SMA MALE
T-FLEX 405, 12.0 IN

PART NO.

CA-8863

REVISION

B

SHEET 1 OF 1

OL8863

2-6-07

JC EB

PART NO. CA-8863

OUTLINE DRAWING